



# Merton Group UK Ltd

*Cleaning and Hygiene Products That Don't Cost the Earth*

## TECHNICAL DATA SHEET

### SILICONE LUBRICANT – 0101

Many industrial applications, including use as a general purpose release agent and as a lubricant where conventional lubricants are contra-indicated. Gives a lasting waterproof film.

- ❖ Aids components assembly by reducing friction.
- ❖ Waterproof film protects against corrosion.
- ❖ Eliminates squeaks and sticking of surfaces in contact.
- ❖ Water Regulations Advisory Scheme (WRAS) – approved product listing number 0511502.
- ❖ Ozone friendly – does not contain chlorofluorocarbons.
- ❖ Colourless, odourless, non-staining and non-tainting.

#### USES:

Long lasting lubrication and protection for many industrial processes in textile, food processing, dairy, packaging, plastic moulding, plumbing and similar industries.

Also machining of natural and synthetic rubber.

Approved for the assembly of water pipes.

#### DIRECTIONS:

Shake can well before each spraying.

Hold can approximately 20cm from surface and spray lightly.

Avoid over spraying.

#### TECHNICAL SPECIFICATION:

Composition: Pure silicone oil.

Appearance: Clear spray

Colour: Colourless

Density: 0.59

Fragrance: Odourless

Stability: Two years minimum

Storage: Pressurised container.

Store out of direct sunlight. Temperature must not exceed 50 degrees.

**Safety: Keep out of the reach of children.**

Extremely flammable, keep away from sources of ignition. Use in well ventilated areas, do not breathe vapour/spray.

