



# Merton Group UK Ltd

*Cleaning and Hygiene Products That Don't Cost the Earth*

## TECHNICAL DATA SHEET

### AMMONIA-FREE METALLISED FLOOR POLISH STRIPPER - 1126

- ❖ No choking ammonia fumes.
- ❖ Quick removal of all emulsion and metallised polishes, even those 'aged on'.
- ❖ Controlled foam for use with suction driers and combined machines.
- ❖ Modern chelating action 'unlocks' metallised polishes.

#### USES:

For the stripping of metallised and non-metallised polish from linoleum, rubber, sealed wood, terrazzo and thermoplastic floors. Effective heavy duty formulation for the removal of impacted dirt from concrete and non-porous surfaces.

#### DIRECTIONS:

Polish stripping – dilute 1 part Ammonia-free Metallised Floor Polish Stripper to 10 parts hot water. Allow to soak on floor for 10 – 15 minutes. Scrub thoroughly, preferably with a scrubbing machine fitted with a nylon scrubbing pad. Remove solution with a mop or suction drier. Rinse thoroughly and allow to dry before reapplying polish.

#### TECHNICAL SPECIFICATION:

**Composition:** A fast acting formulation containing alkali builders, surfactants, penetrating agents and sequestrants.

**Appearance:** Clear liquid

**Colour:** Blue

**Cloud Point:** 38

**Density:** 1.068

**pH:** > 13.5

**Stability:** Two years in unopened container.

**Safety:** Keep locked up & out of reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately and show the container or label.

Causes burns.